

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis

Version: 2
Revision date: 10/02/2020

Page 1 of 11
Print date: 10/02/2020

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: CTX-18 Liquid pH Reducer Saline Electrolysis
Product Code: 0018CM

1.2 Relevant identified uses of the mixture and uses advised against.

pH regulator

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **FLUIDRA COMERCIAL ESPAÑA**
Address: Pintor Velazquez, 10
City: 08213 Polinyà (Barcelona) España
Province: Barcelona
Telephone: telf: 902 42 32 22
Fax: +34 93 713 41 11
E-mail: fds@inquire.com
Web: www.fluidra.es

1.4 Emergency telephone number:

Anti poisoning centre:

ITALY (Rome): 06/305 43 43

ITALY (Milan): 02/66 10 10 29

SPAIN: +34 91 562 04 20

FRANCE (Paris): 01 40 05 48 48 FRANCE (Toulouse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25

PORTUGAL: 808 250 143

BELGIQUE (Brussel): (+34) 070 245 245

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Eye Dam. 1 : Causes serious eye damage.

Met. Corr. 1 : May be corrosive to metals.

Skin Corr. 1A : Causes severe skin burns and eye damage.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H290

May be corrosive to metals.

H314

Causes severe skin burns and eye damage.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis



Version: 2
Revision date: 10/02/2020

Page 2 of 11
Print date: 10/02/2020

P statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P260	Do not breathe vapours.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P501	Dispose of contents/container in accordance with applicable regulations.

Contains:

sulphuric acid
etidronic acid

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 016-020-00-8 CAS No: 7664-93-9 EC No: 231-639-5 Registration No: 01-2119458838-20-XXXX	[1] sulphuric acid	25 - 50 %	Met. Corr. 1, H290 - Skin Corr. 1A, H314	Skin Corr. 1A, H314: C ≥ 15 % Skin Irrit. 2, H315: 5 % ≤ C < 15 % Eye Irrit. 2, H319: 5 % ≤ C < 15 %
CAS No: 2809-21-4 EC No: 220-552-8 Registration No: 01-2119510391-53-XXXX	etidronic acid	1 - 3 %	Acute Tox. 4, H302 - Eye Dam. 1, H318 - Met. Corr. 1, H290	-
Index No: 015-011-00-6 CAS No: 7664-38-2 EC No: 231-633-2 Registration No: 01-2119485924-24-XXXX	[1] phosphoric acid	0 - 10 %	Skin Corr. 1B, H314	Skin Corr. 1B, H314: C ≥ 25 % Skin Irrit. 2, H315: 10 % ≤ C < 25 % Eye Irrit. 2, H319: 10 % ≤ C < 25 %

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis



Version: 2
Revision date: 10/02/2020

Page 3 of 11
Print date: 10/02/2020

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners. The use of personal protective equipment is recommended for people providing first aid (see section 8).

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Contact with eyes may cause irreversible damage.

4.3 Indication of any immediate medical attention and special treatment needed.

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis

Version: 2

Revision date: 10/02/2020

Page 4 of 11

Print date: 10/02/2020

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers at room temperature, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

None in particular.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
sulphuric acid	7664-93-9	European Union [1]	Eight hours		0,05
			Short term		
		United Kingdom [2]	Eight hours	0,05	The mist is defined as the thoracic fraction
			Short term		
phosphoric acid	7664-38-2	European Union [1]	Eight hours		1
			Short term		2
		United Kingdom [2]	Eight hours		1
			Short term		2
		United States [3] (Cal/OSHA)	Eight hours		1
			Short term		3
		United States [4] (NIOSH)	Eight hours		1
			Short term		3
United States [5] (OSHA)	Eight hours		1		
	Short term				

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis

Version: 2

Revision date: 10/02/2020

Page 5 of 11

Print date: 10/02/2020

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[4] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[5] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
sulphuric acid CAS No: 7664-93-9 EC No: 231-639-5	DNEL (Workers)	Inhalation, Long-term, Local effects	0,05 (mg/m ³)
phosphoric acid CAS No: 7664-38-2 EC No: 231-633-2	DNEL (Workers)	Inhalation, Long-term, Local effects	1 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	0,73 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	2 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

CAS: 7664-38-2

TLV TWA - 1 mg/m³

TLV STEL - 3 mg/m³

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %				
Uses:	pH regulator				
Breathing protection:					
PPE:	Particle filter mask				
Characteristics:	«CE» marking, category III. Made of filtering material, it covers nose, mouth and chin.				
CEN standards:	EN 149				
Maintenance:	Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use.				
Observations:	Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.				
Filter Type needed:	P2				
Hand protection:					
PPE:	Protective gloves against chemicals.				
Characteristics:	«CE» marking, category III.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420				
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.				
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
Eye protection:					
PPE:	Protective goggles with built-in frame.				
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.				

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis

Version: 2

Revision date: 10/02/2020

Page 6 of 11

Print date: 10/02/2020

CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.
Skin protection:	
PPE:	Chemical protective clothing
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.
CEN standards:	EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.
PPE:	Work footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid

Colour: Slightly yellowish

Odour: Characteristic

Odour threshold: N.A./N.A.

pH: 0 - 1

Melting point: N.A./N.A.

Boiling Point: 315 - 338 °C

Flash point: 664 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: 20,503

Vapour density: N.A./N.A.

Relative density: 1.33 - 1.37 (20 °C) g/cm³

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: 100 %

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: No applicable

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis

Version: 2
Revision date: 10/02/2020

Page 7 of 11
Print date: 10/02/2020

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Metals.

10.3 Possibility of hazardous reactions.

May be corrosive to metals.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Oxidizing materials.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- Corrosive vapors or gases.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
sulphuric acid CAS No: 7664-93-9 EC No: 231-639-5	Oral	LD50	Rat	5000 mg/kg bw [1]
	Dermal	[1] Hoechst AG (1985): Unveroffentl. Unters. (Ber.-Nr 85.0427)		
	Inhalation			
etidronic acid CAS No: 2809-21-4 EC No: 220-552-8	Oral	LD50	Rat	1878 mg/kg
	Dermal	LD50	Rabbit	> 6000 mg/kg
	Inhalation			
phosporic acid CAS No: 7664-38-2 EC No: 231-633-2	Oral	LD50	Rat	2600 mg/kg [1]
	Dermal	[1] OCDE423		
	Inhalation			

a) acute toxicity;
Not conclusive data for classification.

b) skin corrosion/irritation;
Product classified:
Skin Corrosive, Category 1A: Causes severe skin burns and eye damage.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis



Version: 2
Revision date: 10/02/2020

Page 8 of 11
Print date: 10/02/2020

c) serious eye damage/irritation;
Product classified:
Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;
Not conclusive data for classification.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Not conclusive data for classification.

i) STOT-repeated exposure;
Not conclusive data for classification.

j) aspiration hazard;
Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
sulphuric acid CAS No: 7664-93-9 EC No: 231-639-5	Fish	LC50	Gambusia affinis	42 mg/L (96 h) [1] [1] Wallen et al. (1957), Sewage and Industrial Wastes 29 (6) 695-711
	Aquatic invertebrates	EC50	Daphnia magna	29 mg/L (24 h) [1] [1] IRCHA et Ministère de l'Environnement et du Cadre de Vie, Les produits chimiques dans l'environnement (1981)
	Aquatic plants			
etidronic acid CAS No: 2809-21-4 EC No: 220-552-8	Fish	LC50	Peces	195 mg/l (96 h)
	Aquatic invertebrates	EC50	Daphnia	> 527 mg/kg (96 h)
	Aquatic plants			
phosporic acid CAS No: 7664-38-2 EC No: 231-633-2	Fish			
	Aquatic invertebrates	EC50	Daphnia magna	>100 mg/L (48 h) [1] [1] study report, 2010
	Aquatic plants	EC50	Desmodosmus subspicatus	>100 mg/L (72 h) [1] [1] study report, 2010

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis



Version: 2
Revision date: 10/02/2020

Page 9 of 11
Print date: 10/02/2020

12.2 Persistence and degradability.

There is no information available on the degradability of the substances present. No information is available regarding the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation. Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number.

UN No: UN1760

14.2 UN proper shipping name.

Description:

ADR: UN 1760, CORROSIVE LIQUID, N.O.S. (CONTAINS SULPHURIC ACID), 8, PG II, (E)

IMDG: UN 1760, CORROSIVE LIQUID, N.O.S. (CONTAINS SULPHURIC ACID), 8, PG II

ICAO/IATA: UN 1760, CORROSIVE LIQUID, N.O.S. (CONTAINS SULPHURIC ACID), 8, PG II

14.3 Transport hazard class(es).

Class(es): 8

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 8

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis



Version: 2
Revision date: 10/02/2020

Page 10 of 11
Print date: 10/02/2020



Hazard number: 80
ADR LQ: 1 L
IMDG LQ: 1 L
ICAO LQ: 0,5 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B
Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 1: Slightly hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

Classification codes:

Acute Tox. 4 : Acute toxicity (Oral), Category 4
Eye Dam. 1 : Serious eye damage, Category 1
Met. Corr. 1 : Corrosive to metals, Category 1
Skin Corr. 1A : Skin Corrosive, Category 1A
Skin Corr. 1B : Skin Corrosive, Category 1B

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0018CM-CTX-18 Liquid pH Reducer Saline Electrolysis

Version: 2

Revision date: 10/02/2020

Page 11 of 11

Print date: 10/02/2020

Abbreviations and acronyms used:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- AwSV: Facility Regulations for handling substances that are hazardous for the water.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
- WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.