

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 1 of 16
Print date: 10/02/2020

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: CTX-74 Surfosan Ultra
Product Code: 0074CM

1.2 Relevant identified uses of the mixture and uses advised against.

Sanitizer

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **FLUIDRA COMERCIAL ESPAÑA**
Address: Pintor Velazquez, 10
City: 08213 Polinyà (Barcelona) España
Province: Barcelona
Telephone: telf: 902 42 32 22
Fax: +34 93 713 41 11
E-mail: fds@inquide.com
Web: www.fluidra.es

1.4 Emergency telephone number:

Anti poisoning centre:

ITALY (Rome): 06/305 43 43

ITALY (Milan): 02/66 10 10 29

SPAIN: +34 91 562 04 20

FRANCE (Paris): 01 40 05 48 48 FRANCE (Toulouse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25

PORTUGAL: 808 250 143

BELGIQUE (Brussel): (+34) 070 245 245

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4 : Harmful if inhaled.

Acute Tox. 4 : Harmful if swallowed.

Aquatic Acute 1 : Very toxic to aquatic life.

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.

Eye Dam. 1 : Causes serious eye damage.

Resp. Sens. 1 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT SE 3 : May cause respiratory irritation.

STOT SE 3 : May cause drowsiness or dizziness.

Skin Corr. 1B : Causes severe skin burns and eye damage.

Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 2 of 16
Print date: 10/02/2020



Signal Word:

Danger

H statements:

- H302+H332 Harmful if swallowed or if inhaled.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

P statements:

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P260 Do not breathe dust.
- P264 Wash ... thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P284 [In case of inadequate ventilation] wear respiratory protection.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER or a doctor
- P321 Specific treatment (see ... on this label).
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Contains:

glutaral
quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4

Revision date: 10/02/2020

Page 3 of 16

Print date: 10/02/2020

CAS No: 68424-85-1 EC No: 270-325-2	quaternary ammonium compounds,benzyl-C12-16-alkyldimethyl, chlorides	5 - 25 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 (M=10) - Aquatic Chronic 1, H410 - Eye Dam. 1, H318 - Met. Corr. 1, H290 - Skin Corr. 1B, H314	-
Index No: 605-022-00-X CAS No: 111-30-8 EC No: 203-856-5 Registration No: 01-2119455549-26-XXXX	[1] glutaral	3 - 5 %	Acute Tox. 2, H330 - Acute Tox. 3, H301 - Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 2, H411 - Resp. Sens. 1, H334 - STOT SE 3, H335 - Skin Corr. 1B, H314 - Skin Sens. 1A, H317	STOT SE 3, H335: 0,5 % ≤ C < 5 %
Index No: 607-022-00-5 CAS No: 141-78-6 EC No: 205-500-4 Registration No: 01-2119475103-46-XXXX	[1] ethyl acetate	0 - 10 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 607-130-00-2 CAS No: 123-92-2 EC No: 204-662-3 Registration No: 01-2119548408-32-XXXX	[1] isopentyl acetate	0 - 2.5 %	Flam. Liq. 3, H226	-
Index No: 607-025-00-1 CAS No: 123-86-4 EC No: 204-658-1 Registration No: 01-2119485493-29-XXXX	[1] n-butyl acetate	0 - 20 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance. The use of personal protective equipment is recommended for people providing first aid (see section 8).

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4

Revision date: 10/02/2020

Page 4 of 16

Print date: 10/02/2020

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners. The use of personal protective equipment is recommended for people providing first aid (see section 8).

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

It may cause an allergic reaction in the respiratory system. Chronic exposure can lead to asthma.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate de-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 5 of 16
Print date: 10/02/2020

contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers at room temperature, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
E1	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200

7.3 Specific end use(s).

None in particular.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
glutaral	111-30-8	United Kingdom [1]	Eight hours	0,05	0,2
			Short term	0,05	0,2
ethyl acetate	141-78-6	European Union [2]	Eight hours	200	734
			Short term	400	1468
		United Kingdom [1]	Eight hours	200	
			Short term	400	
		United States [3] (Cal/OSHA)	Eight hours	400	
			Short term		
		United States [4] (NIOSH)	Eight hours	400	
			Short term		
United States [5] (OSHA)	Eight hours	400	1400		
	Short term				
isopentyl acetate	123-92-2	European Union [2]	Eight hours	50	270
			Short term	100	540
		United States [3] (Cal/OSHA)	Eight hours	50	
			Short term	100	
United States	Eight hours	100			

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4

Revision date: 10/02/2020

Page 6 of 16

Print date: 10/02/2020

		[4] (NIOSH)	Short term		
		United States	Eight hours	100	525
		[5] (OSHA)	Short term		
n-butyl acetate	123-86-4	United Kingdom [1]	Eight hours	150	724
			Short term	200	966
		United States [3] (Cal/OSHA)	Eight hours	150	
			Short term	200	
		United States [4] (NIOSH)	Eight hours	150	
			Short term	200	
		United States [5] (OSHA)	Eight hours	150	710
			Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[4] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[5] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
glutaral CAS No: 111-30-8 EC No: 203-856-5	DNEL (Workers)	Inhalation, Long-term, Local effects	0,25 (mg/m ³)
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	734 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Local effects	734 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	367 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	1468 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Local effects	734 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	63 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	37 (mg/kg bw/day)
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	DNEL (Workers)	Inhalation, Long-term, Systemic effects	20,8 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	5,1 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	2,95 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	1,47 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	1,47 (mg/kg bw/day)
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	480 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	102,34 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Systemic effects	960 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Systemic effects	859,7 (mg/m ³)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 7 of 16
Print date: 10/02/2020

	DNEL (Workers)	Inhalation, Long-term, Local effects	480 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	102,34 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	960 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Local effects	859,7 (mg/m ³)
	DNEL (General population)	Oral, Long-term, Systemic effects	3,4 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	3,4 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	aqua (freshwater)	0,24 (mg/L)
	aqua (marine water)	0,024 (mg/L)
	aqua (intermittent releases)	1,65 (mg/L)
	sediment (freshwater)	1,15 (mg/L)
	sediment (marine water)	0,115 (mg/L)
	Soil	0,148 (mg/kg soil dw)
	STP	650 (mg/L)
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	oral (Hazard for predators)	0,2 (g/kg food)
	aqua (freshwater)	0,022 (mg/L)
	aqua (marine water)	0,0022 (mg/L)
	aqua (intermittent releases)	0,22 (mg/L)
	STP	30 (mg/L)
	sediment (freshwater)	17,87 (mg/kg sediment dw)
	sediment (marine water)	1,787 (mg/kg sediment dw)
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	soil	4,15 (mg/kg soil dw)
	aqua (freshwater)	0,18 (mg/l)
	aqua (marine water)	0,018 (mg/l)
	aqua (intermittent releases)	0,36 (mg/l)
	STP	35,6 (mg/l)
	sediment (freshwater)	0,981 (mg/kg sediment dw)
sediment (marine water)	0,0981 (mg/kg sediment dw)	

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

CAS: 111-30-8
TLV TWA - A4 SEN
TLV STEL - C 0,05 ppm - C 0,205 mg/m³, A4 SEN

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

-Continued on next page.-

SAFETY DATA SHEET





(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 8 of 16
Print date: 10/02/2020

Concentration:	100 %				
Uses:	Sanitizer				
Breathing protection:					
PPE:	Particle filter mask				
Characteristics:	«CE» marking, category III. Made of filtering material, it covers nose, mouth and chin.				
CEN standards:	EN 149				
Maintenance:	Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use.				
Observations:	Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.				
Filter Type needed:	P2				
Hand protection:					
PPE:	Protective gloves against chemicals.				
Characteristics:	«CE» marking, category III.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420				
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.				
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
Eye protection:					
PPE:	Protective goggles with built-in frame.				
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.				
CEN standards:	EN 165, EN 166, EN 167, EN 168				
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.				
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.				
Skin protection:					
PPE:	Chemical protective clothing				
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.				
CEN standards:	EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.				
PPE:	Work footwear.				
Characteristics:	«CE» marking, category II.				
CEN standards:	EN ISO 13287, EN 20347				
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.				
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident				

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid

Colour: Orange

Odour: Characteristic

Odour threshold: N.A./N.A.

pH: 5 - 7 (20 °C)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 9 of 16
Print date: 10/02/2020

Melting point: N.A./N.A.
Boiling Point: 94 °C
Flash point: 91 °C
Evaporation rate: N.A./N.A.
Inflammability (solid, gas): N.A./N.A.
Lower Explosive Limit: N.A./N.A.
Upper Explosive Limit: N.A./N.A.
Vapour pressure: 23,503
Vapour density: N.A./N.A.
Relative density: 0.95 - 1.05 (20 °C) g/cm³
Solubility: N.A./N.A.
Liposolubility: N.A./N.A.
Hydrosolubility: 100 %
Partition coefficient (n-octanol/water): N.A./N.A.
Auto-ignition temperature: N.A./N.A.
Decomposition temperature: N.A./N.A.
Viscosity: N.A./N.A.
Explosive properties: N.A./N.A.
Oxidizing properties: No applicable

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A.
Blink: N.A./N.A.
Kinematic viscosity: N.A./N.A.
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:
- Bases.

10.3 Possibility of hazardous reactions.

Neutralization can occur on contact with bases.

10.4 Conditions to avoid.

- Avoid contact with bases.

10.5 Incompatible materials.

Avoid the following materials:
- Bases.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:
- Corrosive vapors or gases.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity
------	----------------

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 10 of 16
Print date: 10/02/2020

	Type	Test	Kind	Value
quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides CAS No: 68424-85-1 EC No: 270-325-2	Oral	LD50	Rat	795 mg/kg
	Dermal	LD50	Rat	1560 mg/kg
	Inhalation			
glutaral CAS No: 111-30-8 EC No: 203-856-5	Oral	LD50	Rat	158 mg/kg
		LD50	Rat	134 mg/kg bw [1] [1] Oyo Yakuri. Pharmacometrics. Vol. 19, Pg. 503, 1980
	Dermal	LD50	Rat	> 2000 mg/kg
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	Oral	LC50	Rat	0,48 mg/l/4 h [1]
		Inhalation		[1] United States Environmental Protection Agency, Office of Pesticides and Toxic Substances. Vol. 8EHQ-1290-1008
	Dermal	LD50	Rabbit	7410 mg/kg bw [1] [1] Aliphatic alcohols and alkyl esters. Narcotic and lethal potencies to tadpoles and to rabbits. Munch, J.C. 1972.
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	Oral	LD50	Rabbit	>5000 mg/kg [1] [1] review: OPDYKE D L J, FOOD COSMET TOXICOL, 13 (5), 545-554, 1975. original source mentioned: Moreno, O.M. (1973). Report to RIFM, 1 February. Opdyke D L J 1975.
		Dermal	LOAEL	Cat
	Inhalation	LD50	Rat	10800 mg/kg bw [1] [1] Acute Toxicity Data. Journal of the American College of Toxicology, Part B. Vol. 1, Pg. 196, 1992
	Dermal	LD50	Rabbit	>17600 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 7, 1974
		Inhalation	LC50	Rat

a) acute toxicity;

Product classified:

Acute toxicity (Inhalation), Category 4: Harmful if inhaled.

Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Inhalation) = 12 mg/l/4 h (Fumes)

ATE (Oral) = 1.923 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin Corrosive, Category 1B: Causes severe skin burns and eye damage.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 11 of 16
Print date: 10/02/2020

d) respiratory or skin sensitisation;

Product classified:

Respiratory sensitiser, Category 1: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
quaternary ammonium compounds,benzyl-C12-16-alkyldimethyl, chlorides CAS No: 68424-85-1 EC No: 270-325-2	Fish	LC50	fish	0.85-1.2 mg/L
	Aquatic invertebrates	EC50	Daphnia	0.02 mg/L
	Aquatic plants	EC50		0.06 mg/L
glutaral CAS No: 111-30-8 EC No: 203-856-5	Fish	LC50	Fish	10.5 mg/l (96 h)
		LC50	Fish	12,2 mg/l (96 h) [1]
	Aquatic invertebrates	EC50	Daphnia	29.73 mg/l (48 h)
		EC50	Crustacean	5,1 mg/l (48 h) [1]
Aquatic plants	EC50	Algae	0.84 mg/l (96 h)	
ethyl acetate	Fish	LC50	Pimephales promelas	230 mg/l (96 h) [1]
				[1] US EPA method E03-05, 1984
Aquatic invertebrates	EC50	Hydra Oligactis (Hydrozoa)	1350 mg/l (48 h) [1]	

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4

Revision date: 10/02/2020

Page 12 of 16

Print date: 10/02/2020

CAS No: 141-78-6 EC No: 205-500-4	Aquatic plants	[1] Aquat. Toxicol. 4, 73 - 82, Slooff, W. 1983
		EC50 Algae 2500 mg/l (96 h) [1]
isopentyl acetate	Fish	[1] Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl.Tech.Inf.Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)
		LC50 Leuciscus idus melanotus 36 mg/l (48 h) [1]
		[1] Fish toxicity (mg/l) Lüdemann WaBoLu Berlin. The methodology was based on the static fish test with the Gold orfe (Leuciscus idus melanotus), according to Mann (1975, 1976), published in Vom Wasser 46 (1976).
CAS No: 123-92-2 EC No: 204-662-3	Aquatic invertebrates	EC50 Daphnia magna Straus 205 mg/l (24 h) [1]
	Aquatic plants	[1] Experimental result, Prüfvorschrift DIN 38412 Teil 11. ErC50 Desmodesmus subspicatus >100 mg/l (48 h) [1]
n-butyl acetate	Fish	[1] Study report, 2010. OECD Guideline 201 (Alga, Growth Inhibition Test).
		LC50 Fish 81 mg/l (96 h) [1]
		[1] Wellens, H. 1982. Comparison of the Sensitivity of Brachydanio rerio and Leuciscus idus by Testing the Fish Toxicity of Chemicals and Wastewaters. Z.Wasser-Abwasser-Forsch. 51(2):49-52 (GER) (ENG ABS). Dawson, G.W., A.L. Jennings, D. Drozdowski, and E. Rider 1977. The Acute Toxicity of 47 Industrial Chemicals to Fresh and Saltwater Fishes. J.Hazard.Mater. 1(4):303-318 (OECDG Data File)
Aquatic invertebrates	EC50 Daphnia sp. 44 mg/l (48 h) [1]	
CAS No: 123-86-4 EC No: 204-658-1	Aquatic plants	[1] publication, 1959 EC50 Desmodesmus subspicatus (reported as Scenedesmus subspicatus) 674.7 mg/l (72 h) [1]
		[1] Method: other: algae growth inhibition test, according to Umweltbundesamt (German Federal Environment Agency) (proposal/draft, version February 1984)

12.2 Persistence and degradability.

There is no information available on the degradability of the substances present.

No information is available regarding the degradability of the substances present.No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
ethyl acetate	0,73	-	9,65 mg/L	Very low

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 13 of 16
Print date: 10/02/2020

N. CAS: 141-78-6	EC No: 205-500-4				
isopentyl acetate		2,26	-	21,5 mg/L	Low
N. CAS: 123-92-2	EC No: 204-662-3				
n-butyl acetate		1,78	-	-	Very low
N. CAS: 123-86-4	EC No: 204-658-1				

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 14 of 16
Print date: 10/02/2020

14.1 UN number.

UN No: UN3265

14.2 UN proper shipping name.

Description:

ADR: UN 3265, CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES / GLUTARAL), 8, PG III, (E)

IMDG: UN 3265, CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES / GLUTARAL), 8, PG III, MARINE POLLUTANT

ICAO/IATA: UN 3265, CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES / GLUTARAL), 8, PG III

14.3 Transport hazard class(es).


Class(es): 8

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

14.6 Special precautions for user.

Labels: 8



Hazard number: 80

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B

Proceed in accordance with point 6.

IMDG Code segregation group: 1 Acids

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): E1

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4
Revision date: 10/02/2020

Page 15 of 16
Print date: 10/02/2020

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 3: Very hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 2 : Acute toxicity (Inhalation), Category 2
Acute Tox. 3 : Acute toxicity (Oral), Category 3
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Eye Dam. 1 : Serious eye damage, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Met. Corr. 1 : Corrosive to metals, Category 1
Resp. Sens. 1 : Respiratory sensitiser, Category 1
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3
Skin Corr. 1B : Skin Corrosive, Category 1B
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1A : Skin sensitiser, Category 1A

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
AwSV: Facility Regulations for handling substances that are hazardous for the water.
BCF: Bioconcentration factor.
CEN: European Committee for Standardization.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



0074CM-CTX-74 Surfosan Ultra

Version: 4

Revision date: 10/02/2020

Page 16 of 16

Print date: 10/02/2020

- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- Log Pow: Logarithm of the partition octanol-water.
- NOEC: No observed effect concentration.
- PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
- WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.