

VITREOUS LINING

Model: SMOOTH ANTISLIP



Pressed and later cooked Vitreous mosaic.

Designed for your safety, we introduce this anti slip mosaic.

Developed and designed to resist chemical products, frost, stain and other hard weather conditions.

Due to its unalterability, easy clean and installation it is an optimum alternative to recover pools, wellness or outdoor-indoor decoration or walk ways. High adherence in wet areas.

TECHNICAL CHARACTERISTICS (CLASE 3)			
UNE-EN ISO	10545-3:1997	Water absorption	< 0.1%
	UNE 67101: 1985 + 1M 1992	Scratch resistance (Mohs)	5
UNE-ENV	10545-12:1997	Slip resistance	Class 3
UNE-EN ISO	10545-12:1997	Frost resistance	Resists
UNE-EN ISO	10545-14:1998	Stain resistance	Class 5 (Hot water)
UNE-EN ISO	10545-13:1998	Chemical resistance	Class UA/UHA resistance
UNE-EN ISO	ISO/DIS 10545-13-17	DFC (Dynamic Friction Coefficient)	Excellent
	DIN 51130: 2010	Critical angle of displacement (ramp)	R13
	DIN 51097	Critical slip angle (barefoot)	Class C

OPTIONS		
NOMINAL FORMAT	THICKNESS	POLYURETHANE
25 x 25 mm	4.2 - 4.7 mm	Available

FINISHED	POLYURETHANE
<p>POLYURETHANE: Both sticked to the rear side of the mosaic plate. It will remain directly to the support.</p>	

PACKAGING					
FORMAT	m ² /Box	m ² /Pallet	Box/Pallet	Kg/Box	Kg/Pallet
25 x 25 mm Standard	2	144	72	18	1316

CODES (CLASS 3)											
FORMAT	GREEN-252	GREEN-253	GREEN-254	GREEN-271	STD. BLUE	POOL BLUE	DARK BLUE	COBALT BLUE	YELLOW	ORANGE	RED
25 x 25 mm POLYURETHANE	54226	54227	54228	54237	54251	54252	54250	54249	54245	54276	54288
CODES (CLASS 3)											
FORMAT	CREAM	BROWN-256	BROWN-273	BROWN-277	PINK	PINK-272	VIOLET-269	VIOLET-270	WHITE	GREY-258	BLACK
25 x 25 mm POLYURETHANE	54267	54229	54239	54243	54289	54238	54235	54236	54256	54231	54277