

POOL LINING MATERIAL

VITREOUS LINING

Model: FOG ANTISLIP



Pressed and later cooked Vitreous mosaic.

Designed for your safety, we introduce this anti slip mosaic.

Developed and designed to resist chemical products, frost, stain and other hard weather conditions.

Due to its unalterability, easy clean and installation it is an optimum alternative to recover pools, wellness or outdoor-indoor decoration or walk ways. High adherence in wet areas.

TECHNICAL CHARACTERISTICS (CLASS 3)			
UNE-EN ISO	10545-3:1997	Water absorption	< 0.1%
	UNE 67101: 1985 + 1M 1992	Scratch resistance (Mohs)	5
UNE-ENV	12633:2003 Anexo A	Slip resistance	Class 3
UNE-EN ISO	10545-12:1997	Frost resistance	Resists
UNE-EN ISO	10545-14:1998	Stain resistance	Class 5 (Hot water)
UNE-EN ISO	10545-13:1998	Chemical resistance	Class UA/UHA resistance
UNE-EN ISO	ISO/DIS 10545-17	DFC (Dynamic Friction Coefficient)	Excellent
	DIN 51130: 2010	Critical angle of displacement (ramp)	R13
	DIN 51097	Critical slip angle (barefoot)	Class C

OPTIONS		
NOMINAL FORMAT	THICKNESS	POLYURETHANE
25 x 25 mm	4.2 - 4.7 mm	Available

FINISHED	POLYURETHANE
<p>POLYURETHANE: Both stuck to the rear side of the mosaic plate. It will remain directly to the support.</p>	

PACKAGING					
FORMAT	m ² /Box	m ² /Pallet	Box/Pallet	Kg/Box	Kg/Pallet
25 x 25 mm Standard	2	144	72	18	1316

CODES (CLASS 3)											
FORMAT	GREEN-202	GREEN-203	GREEN-204	GREEN-211	BLUE FOG	POOL FOG	DARK FOG	YELLOW-207	ORANGE FOG	RED FOG	
25 x 25 mm POLYURETHANE	54199	54200	54201	54508	54278	54282	54279	54204	54280	54283	
CODES (CLASS 3)											
FORMAT	BROWN-206	BROWN-214	BROWN-213	BROWN-217	PINK FOG	PINK-212	VIOLET-210	VIOLET-239	GREY-218	BLACK FOG	
25 x 25 mm POLYURETHANE	54203	54211	54210	54214	54284	54209	54207	54224	54215	54281	