

VITREOUS LINING

Model: GLOSSY



Pressed and later cooked Vitreous mosaic.

Iridescent effect. Bright and colour variations according to the light exposure.

Developed and designed to resist chemical products, frost, stain and other hard weather conditions.

Due to its unalterability, easy clean and installation it is an optimum alternative to recover pools, wellness or outdoor-indoor decoration.


TECHNICAL CHARACTERISTICS

UNE-EN ISO	10545-3:1997	Water absorption	< 0.1%
	UNE 67101: 1985 + 1M 1992	Scratch resistance (Mohs)	5
UNE-EN ISO	10545-12:1997	Frost resistance	Resists
UNE-EN ISO	10545-14:1998	Stain resistance	Class 5 (Hot water)
UNE-EN ISO	10545-13:1998	Chemical resistance	Class UA/UHA resistance

OPTIONS

NOMINAL FORMAT	THICKNESS	POLYURETHANE
25 x 25 mm	4.2 - 4.7 mm	Available






FINISHED

FINISHED	POLYURETHANE
POLYURETHANE: Sticked to the rear side of the mosaic plate. It will remain directly to the support.	


PACKAGING

FORMAT	m ² /Box	m ² /Pallet	Box/Pallet	Kg/Box	Kg/Pallet
25 x 25 mm Standard	2	144	144	18	1316

CODES

					
FORMAT	G-304	G-305	G-306	G-308	G-311
25 x 25 mm POLYURETHANE	54159	54160	54161	54163	54166

CODES

				
FORMAT	G-312	G-319	G-320	G-321
25 x 25 mm POLYURETHANE	54167	57370	57371	57372