## POOL LINING MATERIAL

## **VITREOUS LINING**

## Model: METAL-AIR

MT-03

MT-01

MT-02

Pressed and later cooked Vitreous mosaic.

Iridiscent effect. Metalic finished.

Developed and designed to resist chemical products, frost, stain and other hard weather conditions.

Due to its unalterability, easy clean and installation it is an optimum alternative to recover pools, wellness or outdoor-indoor decoration.

TECHNICAL CHARACTERISTICS				
UNE-EN ISO	10545-3:1997	Water absortion	< 0.1%	
	UNE 67101: 1985 + 1M 1992	Scratch resistence (Mohs)	4	
UNE-EN ISO	10545-12:1997	Frost resistance	Resists	
UNE-EN ISO	10545-14:1998	Stain resistance	Class 5 (Hot water)	
UNE-EN ISO	10545-13:1998	Chemical resistance	Class UA/UHA resistance	

OPTIONS		
NOMINAL FORMAT	THICKNESS	POLYURETHANE
25 x 25 mm	4.2 - 4.7 mm	Available

FINISHED	POLYURETHANE
POLYURETHANE: Sticked to the rear side of the mosaic plate. It will remain directly to the support.	1

PACKAGING					
FORMAT	m²/Box	m²/Pallet	Box/Pallet	Kg/Box	Kg/Pallet
25 x 25 mm Standard	1	144	144	9	1316

CODES				
FORMAT	MT-01	MT-02	MT-03	
25 x 25 mm POLYURETHANE	54394	54395	54396	

