

## VITREOUS LINING

### Model: MOON LUMINISCENT



Pressed and later cooked Vitreous mosaic.

Iridescent effect. After being charged while lights are on, will emit smooth light.

Developed and designed to resist chemical products, frost, stain and other hard weather conditions.

Due to its unalterability, easy clean and installation it is an optimum alternative to recover pools, wellness or outdoor-indoor decoration.


#### TECHNICAL CHARACTERISTICS

UNE-EN ISO	10545-3:1997	Water absorption	< 0.1%
	UNE 67101: 1985 + 1M 1992	Scratch resistance (Mohs)	4
UNE-EN ISO	10545-12:1997	Frost resistance	Resists
UNE-EN ISO	10545-14:1998	Stain resistance	Class 5 (Hot water)
UNE-EN ISO	10545-13:1998	Chemical resistance	Class UA/UHA resistance

#### OPTIONS

NOMINAL FORMAT	THICKNESS	POLYURETHANE
25 x 25 mm	4.2 - 4.7 mm	Available

#### FINISHED

FINISHED	POLYURETHANE
POLYURETHANE: Sticked to the rear side of the mosaic plate. It will remain directly to the support.	

#### PACKAGING

FORMAT	m <sup>2</sup> /Box	m <sup>2</sup> /Pallet	Box/Pallet	Kg/Box	Kg/Pallet
25 x 25 mm Standard	1	144	144	9	1316

#### CODES

	
FORMAT	LU-02
25 x 25 mm POLYURETHANE	54390

