

POOL LINING MATERIAL

VITREOUS LINING

Model: MATTE



Pressed and later cooked Vitreous mosaic. Matte finish.

Developed and designed to resist chemical products, frost, stain and other hard weather conditions.

Due to its unalterability, easy clean and installation it is an optimum alternative to recover pools, wellness or outdoor-indoor decoration.

TECHNICAL CHARACTERISTICS			
UNE-EN ISO	10545-3:1997	Water absorption	< 0.1%
	UNE 67101: 1985 + 1M 1992	Scratch resistance (Mohs)	6
UNE-EN ISO	10545-12:1997	Frost resistance	Resists
UNE-EN ISO	10545-14:1998	Stain resistance	Class 5 (Hot water)
UNE-EN ISO	10545-13:1998	Chemical resistance	Class UA/UHA resistance. Does not resist HCL Class UHC.

OPTIONS		
NOMINAL FORMAT	THICKNESS	POLYURETHANE
25 x 25 mm	4.2 - 4.7 mm	Available

FINISHED	POLYURETHANE
<p>POLYURETHANE: Sticked to the rear side of the mosaic plate. It will remain directly to the support.</p>	

PACKAGING					
FORMAT	m ² /Box	m ² /Pallet	Box/Pallet	Kg/Box	Kg/Pallet
25 x 25 mm Standard	2	144	144	18	1316

CODES

FORMAT	MA-01	MA-02	MA-03	MA-09	MA-10
25 x 25 mm POLYURETHANE	54174	54175	54176	54182	54183