

## VITREOUS LINING

### Model: COLOUR




Cut and coloured glass.

Developed and designed to resist chemical products, frost, stain and other hard weather conditions.

Due to its unalterability, easy clean and installation it is an optimum alternative to recover pools, wellness or outdoor-indoor decoration.

| TECHNICAL CHARACTERISTICS |                           |                           |                     |
|---------------------------|---------------------------|---------------------------|---------------------|
| UNE-EN ISO                | 10545-3:1997              | Water absorption          | < 0.1%              |
|                           | UNE 67101: 1985 + 1M 1992 | Scratch resistance (Mohs) | 4                   |
| UNE-EN ISO                | 10545-12:1997             | Frost resistance          | Resists             |
| UNE-EN ISO                | 10545-14:1998             | Stain resistance          | Class 5 (Hot water) |

| OPTIONS        |           |           |
|----------------|-----------|-----------|
| NOMINAL FORMAT | THICKNESS | FIBER     |
| 25 x 25 mm     | 5 mm      | Available |

| FINISHED  | FIBER   |
|---|---|
| FIBER: Sticked to the rear side of the mosaic plate.<br>It will remain directly to the support. |  |

| PACKAGING           |                     |                        |            |        |           |
|---------------------|---------------------|------------------------|------------|--------|-----------|
| FORMAT              | m <sup>2</sup> /Box | m <sup>2</sup> /Pallet | Box/Pallet | Kg/Box | Kg/Pallet |
| 25 x 25 mm Standard | 1                   | 99                     | 99         | 11.5   | 1138.5    |

### CODES

|                  |   |   |
|------------------|---|---|
|                  |  |  |
| FORMAT           | PCMIX-2011  | PCMIX-2013  |
| 25 x 25 mm FIBER | 45054   | 40823   |