



CTX-600 Anticalcareous

DESCRIPTION:

It is a dispersing and scale inhibitor agent developed for use in swimming pools to remove and control scale formation. It also will prevent plugging of filters and corrosion of metal parts in the recirculation and filtration system.

PROPERTIES:

Appearance	liquid
Colour	Colourless
Density	1,33 – 1,37 g/cm ³
pH (20°C)	> 12.5

CHARACTERISTICS:

Not applicable

DOSAGE AND INSTRUCTIONS FOR USE:

Initial Treatment: Add 2,5 litres of product per 100 m³ of water.

Maintenance Treatment: Add 0,5 litres of product per 100 m³ water once a week.

These doses are merely meant as a guideline and may be modified depending on the hardness of water and its salts.

Those pools, which are not drained during the winter period, should treat with an initial dose of product at the end the bathing season.

Dilute the required dose of product in a container of water and distribute the solution evenly over the pool surface whilst the filtration equipment is in operation.

	<p>Fluidra Comercial España Pintor Velázquez, 10 08213 Polinyà (Barcelona) Spain Tel: 93 713 50 60 Fax: 93 713 41 11 www.certikin.com</p>	
---	---	---

La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.