



CTX-390/GR MultiAction

DESCRIPTION:

Organic compound, especially thought to make that with its only addition to the water in the swimming pool, you manage to eliminate all the bacteria, viruses and micro-organisms in general. It prevents the weeds development and helps to keep the water clear and transparent .

PROPERTIES:

Appearance	crystalline solid
Colour	White
Available chlorine.....	70.2 %
pH (1%).....	1 - 3

CHARACTERISTICS:

Product suitable for the disinfection of swimming pools made with ceramic materials.

Avoid prolonged contact of this product on swimming pools surfaces made with polyester, vinyl or liner. This product discolours these surfaces.

DOSAGE AND INSTRUCTIONS FOR USE:

Initial Treatment: Add 10 grs. of product (0390) per m³ of water. Wait for two hours before adjusting the pH level between 7,2 - 7,6 using either Solid pH Reducer (0010) or pH Enhancer (0020).

Maintenance Treatment: Once the pH level of the water has been adjusted, add 1 or 2 grams of product per m³ of water daily.

This dose is merely meant as a guideline and may be modified according to differing characteristics of the pool or climate.

The Initial treatment (Super chlorination) should be repeated whenever the water does not appear transparent.

	Fluidra Comercial España Pintor Velázquez, 10 08213 Polinyà (Barcelona) Spain Tel: 93 713 50 60 Fax: 93 713 41 11 www.certikin.com	
---	--	---

La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.



Introduce the necessary dose of product inside the skimmers and then turn on the filter equipment; in this way the product will dissolve when it begins to move through the skimmers.

It is also possible to pour the dose of product equally over the surface of the swimming pool, preferably during the evening and when there are no swimmers in the pool.

The level of free residual chlorine should be between 0,5 - 2 mg/l. This level is easily determined using a chlorine and pH test kit, and should be measured at least twice daily.



Fluidra Comercial España
Pintor Velázquez, 10
08213 Polinyà (Barcelona) Spain
Tel: 93 713 50 60
Fax: 93 713 41 11 www.certikin.com



La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.