



CTX-57 Netafilter

DESCRIPTION:

Liquid acidic product for elimination of encrustations produced by water salts and dirt deposits formed inside sand filters.

PROPERTIES:

Appearance	liquid
Colour	yellow
Density	1,13 - 1,17 g/cm ³
pH.....	0

CHARACTERISTICS:

Liquid product which gives off smoke or vapours annoying to the user.

Suitable for the cleaning of stainless steel or polyester filters.

Does not generate foam. Produces effervescence as the lime dissolves.

Easy to apply and easily rinsed running water.

DOSAGE AND INSTRUCTIONS FOR USE:

This treatment is valid only for filters with silex or sand filtering charge.

With the filter at standstill and uncovered, drain all the water from inside the filter through the bottom valve.

Shut the drain valve and pour 2 litres of water through the filter mouth, followed by 2 litres of product NETAFILTER for every 10 Kg of sand or silex approximately.

This added solution must cover the level of the sand by 20 to 30 cm.

Leave the product to react with the lime and dirtiness present in the filter. When the effervescence (bubbles) ceases after a prudential time has elapsed (some 4 to 8 hours), shut the filter cover, move the valve cock to washing position and pass water through the filter to rinse it out.



Fluidra Comercial España
Pintor Velázquez, 10
08213 Polinyà (Barcelona) Spain
Tel: 93 713 50 60
Fax: 93 713 41 11 www.certikin.com



La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.



Note:

The rinsing water must be poured directly down the drain.

During rinsing a check should be made to ensure that the pH of the emerging waste water is the same as that of the incoming water. When this point is reached the filter cleaning process can be considered complete.

Once the filter has been inspected, repeat the treatment if any remain of caked or hardened sand are found.



Fluidra Comercial España
Pintor Velázquez, 10
08213 Polinyà (Barcelona) Spain
Tel: 93 713 50 60
Fax: 93 713 41 11 www.certikin.com



La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.