



## CTX-602 Anticalcareous Eco

### DESCRIPTION:

It is a dispersing and scale inhibitor agent developed for use in swimming pools to remove and control scale formation and avoids the formation of stains in the pool, due to the iron present in the water.

### PROPERTIES:

Appearance .....	liquid
Colour .....	Colourless
Density .....	1,04 – 1,08 g/cm <sup>3</sup>

### CHARACTERISTICS:

This product is compatible with the INQUIDE disinfectants, algicides and biocides.

### DOSAGE AND INSTRUCTIONS FOR USE:

**Initial Treatment:** On beginning the bathing season, add 2 l. of product (0602) to the water of the swimming pool for each 100 m<sup>3</sup> of water.

**Maintenance Treatment:** Add 1,5 - 2 l. of product (0602) each 100 m<sup>3</sup> of water once a week.

These dosages are for guidance only and can be modified in accordance with the hardness and the salt contents of the water. In swimming pools with hardness greater than 35 °F and temperatures of 28 °C, the dosage of product should be increased by 25 to 50 %.

**Important:** Whenever the water contains iron, it is important to add the product to the water of the swimming pool before chlorination or any oxidation treatment.

Dilute the required dose of product in a container of water and distribute the solution evenly over the pool surface whilst the filtration equipment is in operation.

	Fluidra Comercial España Pintor Velázquez, 10 08213 Polinyà (Barcelona) Spain Tel: 93 713 50 60 Fax: 93 713 41 11 <a href="http://www.certikin.com">www.certikin.com</a>	
---	--	---

*La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.*