



## **CTX-342 MultiAction 200gr Special liner**

### **DESCRIPTION:**

Solid compound in tablets, especially thought to make that with its only addition to the water in the swimming pool, you manage to eliminate all the bacteria, viruses and micro-organisms in general. It prevents the weeds development and helps to keep the water clear and transparent .

Product free of metals (such as copper). Ideal for easy and effective maintenance of pool water public or private use.

### **PROPERTIES:**

Appearance .....	solid in tablets (200 g)
Colour .....	White
Available chlorine.....	82%
pH (5%).....	2,5 - 3

### **CHARACTERISTICS:**

Free of metals (copper).

Ideal for liner and polyester pools. Using this product there is no danger of staining caused by heavy metals.

### **DOSAGE AND INSTRUCTIONS FOR USE:**

**Initial treatment:** Add 15 gram of Dichloroisocyanuric Acid Granules (0200GR) for every m<sup>3</sup> water. After 2 hours, adjust the water pH between 7,2 and 7,6 using either Solid pH Reducer (0010) or pH Enhancer (0020).

**Maintenance treatment:** Once we have the water pH adjusted, add 1 tablet of Multiaction 200g (without copper) for every 20 m<sup>3</sup> water during 7-10 days.

	Fluidra Comercial España Pintor Velázquez, 10 08213 Polinyà (Barcelona) Spain Tel: 93 713 50 60 Fax: 93 713 41 11 <a href="http://www.certikin.com">www.certikin.com</a>	
---	--	---

*La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.*



These doses are the ones suggested and can be modified according to the own characteristics of every swimming pool, climate, etc.

The initial treatment (Superchloring) will have to be repeated whenever you notice a lack of transparency in the water.

Introduce the necessary multi-action tablets 200g (without copper) doses inside the skimmers. Connect the filtering equipment after and you will have the product dissolved in the water, because water will be flowing through the skimmers.

It is essential that the entire volume of the pool water is recirculated through the scrubber equipment daily.

The free residual chlorine should be between 0.5-2 mg/l. This value is easily measured using a chlorine analyzer case and pH. This check must be made at least 2 times a day.

#### Recommendations:

Keep water passage completely open on the skimmers and sump during the filtration process.

It is advisable to introduce the new dose of multi-action 200g (without copper) when the tablets that are inside the skimmers have been reduced 10% of its original weight.



Fluidra Comercial España  
Pintor Velázquez, 10  
08213 Polinyà (Barcelona) Spain  
Tel: 93 713 50 60  
Fax: 93 713 41 11 [www.certikin.com](http://www.certikin.com)



*La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.*