



CTX-391 Multiaction antical

PRODUCT DESCRIPTION:

Solid compound in bars, specially formulated to eliminate, in just one application, bacteria, virus and micro-organisms in general. It also prevents algae from growing, keeps the water crystal clear and avoids lime incrustations.

PRODUCT QUALITIES:

Aspect	Solid in bars
Colour	White and blue
Content in useful chlorine.....	83 %
pH (1%).....	2.5 – 3

PRODUCT CHARACTERISTICS:

Calcic hardness indicates Calcium content in water.

There can appear problems with incrustations and cloudy waters when hardness is over the range of 175 and 300 CaCO₃ ppm. This is caused by the use of chemical products, which contain Calcium ions.

In order to prevent this kind of problems, **0391 ANTICAL TRIPLEX-200** has got additives which prevent and control calcareous incrustations.

Furthermore, **0391 ANTICAL TRIPLEX-200** also helps to prevent the filters blockage, the corrosiveness of recirculation and filtration systems and the appearance of stains because of the iron that has been dissolved in water.

This product must not come into direct contact with swimming-pools made with polyester and vinyl or the well-painted ones because it can cause discolorations.

	Fluidra Comercial España Pintor Velázquez, 10 08213 Polinyà (Barcelona) Spain Tel: 93 713 50 60 Fax: 93 713 41 11 www.certikin.com	
---	--	---

La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.



DOSAGE AND INSTRUCTIONS FOR USE:

Initial treatment: Add 15 g. of Granulated Dichloride for every m³ of water. After 2 hours, adjust water pH between 7.2 and 7.6, using pH Solid Minorizer (0010) or pH Solid Increaser (0020).

Maintenance treatment: Once we have the adjusted water pH, add **0391 ANTICAL TRIPLEX-200** bar for every 20 m³ of water every 7 or 10 days.

These doses are approximate and can be modified depending on the swimming-pool, on the weather, etc.

The initial treatment (Superchlorination) must be repeated every time water is not transparent.

Put the necessary dose of **0391 ANTICAL TRIPLEX-200** in the skimmers; secondly, put the filtration equipment into operation. The product, once water runs through the skimmers, will be dissolved.

It is essential that the whole amount of the swimming-pool water is purified daily.

The residual chlorine must range from 0.5 to 2 mg/l. This value can be easily measured by the test kits at least twice a day.



Fluidra Comercial España
Pintor Velázquez, 10
08213 Polinyà (Barcelona) Spain
Tel: 93 713 50 60
Fax: 93 713 41 11 www.certikin.com



La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.