



CTX-55 De-scaler for Filters

DESCRIPTION:

A solid of acidic properties, the use of which eliminates the encrustations produced by salts and dirt present in the pool water and deposited inside sand filters.

The number of backwashes that are normally carried out in a filter are not usually enough to eliminate all the particles deposited in them. These particles cause the filtering bed (sand) to become congested so as to make the free circulation of the water inside the filter very difficult. This in turn causes the filter bed to rupture and so-called preferential channels are formed allowing the water to pass easily through the filter without being properly filtered the sand bed.

PROPIETIES:

Appearance Crystalline solid
 Colour White
 Density 2,12 g/c.c
 pH of 1 % solution 1,18

DOSAGE AND INSTRUCTIONS FOR USE

These treatments are suitable only for those filters with silex or sand used as filter media.

1. - Periodic cleaning of the filter.

Place 0,5 Kg. of product in the pre-filter of the pump or in the skimmer. Set the selector valve to filtration position and work the filter for a short space of time so that the dissolved product has enough time to reach the inside of the filter. Stop the filter and allow the product to act for approximately one hour. Follow this with a thorough backwash.

	<p>Fluidra Comercial España Pintor Velázquez, 10 08213 Polinyà (Barcelona) Spain Tel: 93 713 50 60 Fax: 93 713 41 11 www.certikin.com</p>	
---	---	---

La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.



2. - Annual cleaning of the filter.

The cleaning is carried out as follows:

- A) Completely drain the water from the inside of the filter.
- B) Open the filter from the lid and pour in a 10% solution of product (1 Kg. of product for every 10 litres of water), ensuring as far as possible that the solution covers the filtering load.
- C) Allow the product to react for approximately 8 hours.
- D) Close the filter and proceed with a thorough backwash.

PRESENTATION

In 1,5 - 15 and 40 Kgs. drums.



Fluidra Comercial España
Pintor Velázquez, 10
08213 Polinyà (Barcelona) Spain
Tel: 93 713 50 60
Fax: 93 713 41 11 www.certikin.com



La información contenida en este folleto es según nuestro criterio correcta. No obstante, como las condiciones en las que se usa este producto caen fuera de nuestro control, no podemos responsabilizarnos de las consecuencias de su mala utilización.