(in accordance with Regulation (EU) 2015/830)

ASTRAL Liquid Clarifier



ASTRALPOOL

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: ASTRAL Liquid Clarifier

1.2 Relevant identified uses of the mixture and uses advised against.

Flocculant

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: FLUIDRA COMMERCIAL, S.A.U.

Address: Avda. Francesc Macià, 60, 20^a planta

City: 08208 Sabadell
Province: (Barcelona) Spain
Telephone: Tel: +34 93 724 39 00
Fax: Fax: +34 93 724 29 93
E-mail: fds@inquide.com
Web: www.astralpool.com

1.4 Emergency telephone number:

Anti poisoning centre:

ITALY (Rome): 06/305 43 43 ITALY (Milan): 02/66 10 10 29

SPAIN: +34 91 562 04 20

FRANCE (Paris): 01 40 05 48 48 FRANCE (Tolousse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25

PORTUGAL: 808 250 143

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Eye Dam. 1 : Causes serious eye damage. Met. Corr. 1 : May be corrosive to metals.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H318 Causes serious eye damage. H290 May be corrosive to metals.

P statements:

(in accordance with Regulation (EU) 2015/830)

ASTRAL Liquid Clarifier



 Version: 1
 Page 2 of 9

 Revision date: 11/01/2017
 Print date: 11/01/2017

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or a doctor

Contains:

Aluminum chloride hydroxide sulfate

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

				(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit	
CAS No: 39290-78-3 EC No: 254-400-7 Registration No: 01- 2119531540-51-XXXX	Aluminum chloride hydroxide sulfate	3 - 25 %	Eye Dam. 1, H318 - Met. Corr. 1, H290	-	

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eve contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

(in accordance with Regulation (EU) 2015/830)

ASTRAL Liquid Clarifier





SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO_2 . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section $\overline{8}$. Never use pressure to empty the containers. They are not pressure-resistant containers. In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

None in particular.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

(in accordance with Regulation (EU) 2015/830)

ASTRAL Liquid Clarifier



 Version: 1
 Page 4 of 9

 Revision date: 11/01/2017
 Print date: 11/01/2017

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
Aluminum chlorido hudrovido culfato	DNEL	Inhalation, Long-term, Systemic effects	1,8
Aluminum chloride hydroxide sulfate N. CAS: 39290-78-3	(Workers)		(mg/m3)
	DNEL	Oral, Long-term, Systemic effects	0,5
N. CE: 254-400-7	(Workers)		(ma/ka)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

CAS: 39290-78-3 TLV TWA - 2 mg/m3 (Al) **8.2 Exposure controls.**

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %				
Uses:	Flocculant				
Breathing protection:					
If the recommended	If the recommended technical measures are observed, no individual protection equipment is necessary.				
Hand protection:					
PPE:	Work gloves.				
Characteristics:	«CE» marking, category I.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420				
	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible.				
Maintenance:	Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or				
	adhesives.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight.				
	Always use with clean, dry hands.				
Material:	PVC (polyvinyl chloride) Breakthrough time > 480 Material thickness 0,35				
	(min.): (mm):				
Eye protection:					
PPE:	Protective goggles with built-in frame.				
Characteristics: «CE» marking, category II. Eye protector with built-in frame for protection against					
CEN	dust, smoke, fog and vapour.				
CEN standards:	EN 165, EN 166, EN 167, EN 168				
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should				
	be disinfected periodically following the manufacturer's instructions.				
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses,				
Skin protection:	scraping etc.				
PPE:	Protective clothing				
ITTL.	Protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in				
Characteristics:	order not to obstruct the user's movements.				
CEN standards:	EN 340				
	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by				
Maintenance:	the manufacturer.				
	The protective clothing should offer a level of comfort in line with the level of protection provided in				
Observations:	terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level				
	of activity and the expected time of use.				
PPE:	Work footwear.				
Characteristics:	«CE» marking, category II.				
CEN standards:	EN ISO 13287, EN 20347				
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should				
rialiteriance.	not be used by other people.				
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any				
Obsci vations.	injury resulting from an accident				

(in accordance with Regulation (EU) 2015/830)

ASTRAL Liquid Clarifier

 Version: 1
 Page 5 of 9

 Revision date: 11/01/2017
 Print date: 11/01/2017

ASTRALPOOL

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance:Liquid Colour: Colourless

Odour:Characteristic (agreeable)
Odour threshold:N.A./N.A.
pH:3.5 - 4.5 (1%)
Melting point:N.A./N.A.
Boiling Point: 100 - 120 °C
Flash point: N.A./N.A.
Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:N.A./N.A.

Relative density:1.18 - 1.22 (25 °C) g/cm³

Solubility: N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: 100 % (20 °C)

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A. Oxidizing properties: No aplicable

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A. Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Bases.

10.3 Possibility of hazardous reactions.

Neutralization can occur on contact with bases.

10.4 Conditions to avoid.

- Avoid contact with bases.

10.5 Incompatible materials.

Avoid the following materials:

- Bases.

10.6 Hazardous decomposition products.


Depending on conditions of use, can be generated the following products:

- Corrosive vapors or gases.

SECTION 11: TOXICOLOGICAL INFORMATION.

(in accordance with Regulation (EU) 2015/830)

ASTRAL Liquid Clarifier



ASTRALPOOL

 Version: 1
 Page 6 of 9

 Revision date: 11/01/2017
 Print date: 11/01/2017

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
Name	Type	Test	Kind	Value
	Oral	LD50	Rat	2630 mg/kg
Aluminum chloride hydroxide sulfate	Dermal	LD50	Rat	> 2000 mg/kg
CAS No: 39290-78-3	Inhalation	LC50	Rat	> 5 mg/l (4 h)

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
Name	Туре	Test	Kind	Value
	Fish	LC50 [1] TG 203	Fish	> 1000 mg/l (96 h) [1]
Aluminum chloride hydroxide sulfate	Aquatic invertebrates	EC50 [1] TG 202	Daphnia	98 mg/l (48 h) [1]
CAS No: 39290-78-3	Aquatic plants	EC50	Algae	14 mg/l (72 h) [1]

(in accordance with Regulation (EU) 2015/830)

ASTRAL Liquid Clarifier



ASTRALPOOL

 Version: 1
 Page 7 of 9

 Revision date: 11/01/2017
 Print date: 11/01/2017

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
Name	Log Pow	BCF	NOECs	Level
Aluminum chloride hydroxide sulfate	0		_	Voncloss
N. CAS: 39290-78-3 EC No: 254-400-7	0	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport

<u>Land</u>: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

<u>Sea</u>: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

(in accordance with Regulation (EU) 2015/830)

ASTRAL Liquid Clarifier



ASTRALPOOL

 Version: 1
 Page 8 of 9

 Revision date: 11/01/2017
 Print date: 11/01/2017

14.1 UN number. UN No: UN3264

14.2 UN proper shipping name.

Description:

ADR: UN 3264, CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (CONTAINS ALUMINUM CHLORIDE HYDROXIDE SULFATE),

8, PG III, (E)

IMDG: UN 3264, CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (CONTAINS ALUMINUM CHLORIDE HYDROXIDE SULFATE),

8, PG III

ICAO: UN 3264, CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (CONTAINS ALUMINUM CHLORIDE HYDROXIDE SULFATE),

8, PG III

14.3 Transport hazard class(es).

Class(es): 8

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 8



Hazard number: 80 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B

Proceed in accordance with point 6. IMDG Code segregation group: 1 Acids

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

SECTION 16: OTHER INFORMATION.

(in accordance with Regulation (EU) 2015/830)

ASTRAL Liquid Clarifier



 Version: 1
 Page 9 of 9

 Revision date: 11/01/2017
 Print date: 11/01/2017

Complete text of the H phrases that appear in section 3:

H290 May be corrosive to metals. H318 Causes serious eye damage.

Classification codes:

Eye Dam. 1 : Serious eye damage, Category 1 Met. Corr. 1 : Corrosive to metals, Category 1

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
39290-78-3	Aluminum chloride hydroxide sulfate	Registered

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.
 PPE: Personal protection equipment.
 IATA: International Air Transport Association.
 ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

Log Pow: Logarithm of the partition octanol-water. NOEC: No observed effect concentration.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.