(in accordance with Regulation (EU) 2015/830)



# **ASTRAL MULTIACTION GRANULAR**

 Version: 1
 Page 1 of 12

 Revision date: 19/07/2016
 Print date: 19/07/2016

# SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

### 1.1 Product identifier.

Product Name: ASTRAL MULTIACTION GRANULAR

### 1.2 Relevant identified uses of the mixture and uses advised against.

Desinfectant-algaecide-flocculant

## Uses advised against:

Uses other than those recommended.

## 1.3 Details of the supplier of the safety data sheet.

Company: FLUIDRA COMMERCIAL, S.A.U.

Address: Avda. Francesc Macià, 60, 20<sup>a</sup> planta

City: 08208 Sabadell
Province: (Barcelona) Spain
Telephone: +34 93 724 39 00
Fax: +34 93 724 29 93
E-mail: fds@astralpool.com
Web: www.astralpool.com

## 1.4 Emergency telephone number:

Anti poisoning centre:

ITALY (Rome): 06/305 43 43 ITALY (Milan): 02/66 10 10 29

SPAIN: +34 91 562 04 20

FRANCE (Paris): 01 40 05 48 48 FRANCE (Tolousse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25

PORTUGAL: 808 250 143

### **SECTION 2: HAZARDS IDENTIFICATION.**

## 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4: Harmful if swallowed. Aquatic Acute 1: Very toxic to aquatic life.

Aquatic Chronic  ${\bf 1}$ : Very toxic to aquatic life with long lasting effects.

Eye Dam. 1 : Causes serious eye damage. Ox. Sol. 2 : May intensify fire; oxidiser. STOT SE 3 : May cause respiratory irritation.

### 2.2 Label elements.

# Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:









Signal Word: **Danger** 

H statements:

H272 May intensify fire; oxidiser.

(in accordance with Regulation (EU) 2015/830)



# **ASTRAL MULTIACTION GRANULAR**

 Version: 1
 Page 2 of 12

 Revision date: 19/07/2016
 Print date: 19/07/2016

H302 Harmful if swallowed.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

P statements:

P221 Take any precaution to avoid mixing with combustibles.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P270 Do no eat, drink or smoke when using this product.

P261 Avoid breathing dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash hands thoroughly after handling.

P370+P378 In case of fire: Use appropriate extinguishing products.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P102 Keep out of reach of children.

P405 Store locked up.

P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with applicable regulations.

**EUH statements:** 

EUH031 Contact with acids liberates toxic gas.

EUH206 Warning! Do not use together with other products. May release dangerous gases (chlorine).

Contains: symclosene Aluminiumsulfate

copper sulphate pentahydrate

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.**

## 3.1 Substances.

Not Applicable.

## 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit
Index No: 613-031- 00-5 CAS No: 87-90-1 EC No: 201-782-8	symclosene	70 - 80 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Irrit. 2, H319 - Ox. Sol. 2, H272 - STOT SE 3, H335	-
CAS No: 10043-01-3 EC No: 233-135-0 Registration No: 01- 2119531538-36-XXXX	Aluminiumsulfate	3 - 25 %	Eye Dam. 1, H318	-

(in accordance with Regulation (EU) 2015/830)





 Version: 1
 Page 3 of 12

 Revision date: 19/07/2016
 Print date: 19/07/2016

CAS No: 7758-99-8 EC No: 231-847-6	copper sulphate pentahydrate	2.5 - 10 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315	-
---------------------------------------	------------------------------	------------	--	---

<sup>(\*)</sup> The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

### **SECTION 4: FIRST AID MEASURES.**

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### Inhalation.

If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

#### Eve contact

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

Remove the person from the contaminated area.

If the person is unconscious, lay on his side with head lower and knees half bent.

Keep body temperature.

Move to the intoxicated person to a hospital and, whenever possible, bring the container or label.

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the

product must be rinsed immediately with plenty of running water and possibly with soap.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

Remove the person from the contaminated area.

If the person is unconscious, lay on his side with head lower and knees half bent.

Keep body temperature.

Move to the intoxicated person to a hospital and, whenever possible, bring the container or label.

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the

product must be rinsed immediately with plenty of running water and possibly with soap.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

# 4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Contact with skin: irritation. Contact with eyes: irritation.

Swallowing: irritation to mucosal and digestive tract corrosion.

Nausea Vomiting

Delayed hypersensitivity

Hepatic-renal disorders and neurotoxic.

<sup>\*</sup> See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

(in accordance with Regulation (EU) 2015/830)

# **ASTRAL**POOL



Inhalation: irritation to mucosal and respiratory tract.

Contact with skin: irritation. Contact with eyes: irritation.

Swallowing: irritation to mucosal and digestive tract corrosion.

Nausea Vomiting

Delayed hypersensitivity

Hepatic-renal disorders and neurotoxic.

Inhalation: irritation to mucosal and respiratory tract.

### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

The dilution with water or milk is appropiate if there was no vomiting (adults from 120 - 140 ml,

children do not exceed 120 ml).

Contraindication: Neutralization with bicarbonate.

In case of ingestion, assess the performance of an endoscopy.

Treat symptomatically.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

The dilution with water or milk is appropiate if there was no vomiting (adults from 120 - 140 ml,

children do not exceed 120 ml).

Contraindication: Neutralization with bicarbonate.

In case of ingestion, assess the performance of an endoscopy.

Treat symptomatically.

### **SECTION 5: FIREFIGHTING MEASURES.**

### 5.1 Extinguishing media.

## Recommended extinguishing methods.

Extinguisher powder or  $\overline{CO_2}$ . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

## 5.2 Special hazards arising from the mixture.

### Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product Dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

# 6.3 Methods and material for containment and cleaning up.

The contaminated area should be immediately cleaned with an appropriate de-contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

(in accordance with Regulation (EU) 2015/830)

# **ASTRAL MULTIACTION GRANULAR**



 Version: 1
 Page 5 of 12

 Revision date: 19/07/2016
 Print date: 19/07/2016

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

### **SECTION 7: HANDLING AND STORAGE.**

## 7.1 Precautions for safe handling.

For personal protection, see section  $\bar{8}$ . Never use pressure to empty the containers. They are not pressure-resistant containers. In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

## 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between at room temperature, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III)::

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
P8	OXIDISING LIQUIDS AND SOLIDS	50	200

### 7.3 Specific end use(s).

None in particular.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.**

# 8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
Aluminiumanulfaha	DNEL (Workers)	Dermal, Long-term, Local effects	10 (mg/kg)
Aluminiumsulfate N. CAS: 10043-01-3 N. CE: 233-135-0	DNEL (General population)	Oral, Long-term, Systemic effects	5 (mg/kg)
N. CE. 255-155-0	DNEL (Workers)	Dermal, Long-term, Systemic effects	1,8 (mg/m3)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
Aluminiumsulfate	Water (freshwater)	34,6 (mg/kg)
N. CAS: 10043-01-3	Sediment (marine water)	3,46 (mg/kg)
N. CE: 233-135-0	Soil	33,1 (mg/kg)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

CAS: 87-90-1

TLV TWA - 0.5 ppm (1.5 mg/m3) Cl gas TLV STEL - 1 ppm (3.0 mg/m3) Cl gas

CAS: 10043-01-3

(in accordance with Regulation (EU) 2015/830)



Version: 1 Page 6 of 12 **Revision date: 19/07/2016** Print date: 19/07/2016

TLV TWA - 2 mg/m3 (AI) 8.2 Exposure controls.

### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Desinfectant-algaecide-flocculant
Breathing protect	
	technical measures are observed, no individual protection equipment is necessary.
Hand protection:	Todal model of the observed no manager procession of the model of the
PPE:	Non-disposable protective gloves against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.
Material:	PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm): 0,35
Eye protection:	
PPE:	Protective goggles against particle impacts.
Characteristics:	«CE» marking, category II. Eye protector against dust and smoke.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.
Skin protection:	
PPE:	Chemical protective clothing
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.
CEN standards:	EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by
- rantecriancer	the manufacturer.
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.
PPE:	Anti-static safety footwear against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.**

## 9.1 Information on basic physical and chemical properties.

Appearance: Granulate Colour: White anb blue Odour:Similar to bleach Odour threshold: N.A./N.A. pH:1 - 3 (1%) Melting point: > 230 °C Boiling Point: N.A./N.A.

-Continued on next page.-

(in accordance with Regulation (EU) 2015/830)

# ASTRALPOOL 🔨

# **ASTRAL MULTIACTION GRANULAR**

 Version: 1
 Page 7 of 12

 Revision date: 19/07/2016
 Print date: 19/07/2016

Flash point: N.A./N.A. Evaporation rate: N.A./N.A.

Inflammability (solid, gas): > 250 °C Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:N.A./N.A. Relative density:N.A./N.A. Solubility: N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: 1°C

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A. Explosive properties: N.A./N.A. Oxidizing properties: Si

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

### 9.2. Other information.

### **SECTION 10: STABILITY AND REACTIVITY.**

### 10.1 Reactivity.

Contact with acids liberates toxic gas.

If the storage conditions are satisfied, does not produce dangerous reactions.

### 10.2 Chemical stability.

Unstable in contact with:

- Bases.

## 10.3 Possibility of hazardous reactions.

Warning! Do not use together with other products. May release dangerous gases (chlorine).

May intensify fire; oxidiser.

Neutralization can occur on contact with bases.

## 10.4 Conditions to avoid.

Avoid the following conditions:

- Contact with incompatible materials.
- Avoid contact with bases.

### 10.5 Incompatible materials.

Avoid the following materials:

- Bases.
- Flammable materials.
- Explosives materials.
- Toxic materials.
- Corrosive materials.

## 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- Oxygen.
- Corrosive vapors or gases.
- Oxidizing gases or vapors.

## **SECTION 11: TOXICOLOGICAL INFORMATION.**

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

## 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

(in accordance with Regulation (EU) 2015/830)



# **ASTRAL MULTIACTION GRANULAR**

 Version: 1
 Page 8 of 12

 Revision date: 19/07/2016
 Print date: 19/07/2016

### Toxicological information about the substances present in the composition.

Nama		Acute toxicity			
ı	Name		Test	Kind	Value
			LD50	Rat	490 mg/kg [1]
		Oral			
			[1] EPA O	PP 81-1	
symclosene			LD50	Rabbit	>2000 mg/kg [1]
		Dermal			
			[1] EPA O	PP 81-2	
		Inhalation			
CAS No: 87-90-1	EC No: 201-782-8	2			
			LD50	Rat	>2000 mg/kg [1]
		Oral			
			[1] OCDE		
Aluminiumsulfate			LD50	Rabbit	>5000 mg/kg [1]
		Dermal			
			[1] OCDE	402	
		Inhalation			
CAS No: 10043-01-3	EC No: 233-135-0	Imaladon			

a) acute toxicity;

Product classified:

Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Oral) = 617 mg/kg

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

## **SECTION 12: ECOLOGICAL INFORMATION.**

# 12.1 Toxicity.

(in accordance with Regulation (EU) 2015/830)



# **ASTRAL MULTIACTION GRANULAR**

 Version: 1
 Page 9 of 12

 Revision date: 19/07/2016
 Print date: 19/07/2016

Name		Ecotoxicity			
		Туре	Test	Kind	Value
		Fish	LC50	Fish	0.32 mg/l (96h)
symclosene		Aquatic invertebrates	LC50	Daphnia	0.21 mg/l (48h)
CAS No: 87-90-1	EC No: 201-782-8	Aquatic plants			
		Fish	LC50	Fish	> 1000 mg/l (96 h)
Aluminiumsulfate		Aquatic invertebrates	LC50	Daphnia	> 160 mg/l (48h)
CAS No: 10043-01-3	EC No: 233-135-0	Aquatic plants			

### 12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potencial.

No information is available regarding the bioaccumulation of the substances present.

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

## 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## **SECTION 13 DISPOSAL CONSIDERATIONS.**

## 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

## **SECTION 14: TRANSPORT INFORMATION.**

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

<u>Sea:</u> Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

(in accordance with Regulation (EU) 2015/830)

# **ASTRAL MULTIACTION GRANULAR**



 Version: 1
 Page 10 of 12

 Revision date: 19/07/2016
 Print date: 19/07/2016

**14.1 UN number.** UN No: UN1479

## 14.2 UN proper shipping name.

Description: UN 1479, OXIDIZING SOLID, N.O.S. (CONTAINS SYMCLOSENE), 5.1, PG II, (E)

### 14.3 Transport hazard class(es).

Class(es): 5.1

### 14.4 Packing group.

Packing group: II

### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

### 14.6 Special precautions for user.

Labels: 5.1



Hazard number: 50 ADR LQ: 1 kg

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-Q Proceed in accordance with point 6.

# 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code.

The product is not transported in bulk.

## **SECTION 15: REGULATORY INFORMATION.**

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

See annex I of the Directive 96/82/EC of 9 December 1996 on the control of major-accident hazards involving dangerous substances.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P8

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

### 15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

## **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

(in accordance with Regulation (EU) 2015/830)



# **ASTRAL MULTIACTION GRANULAR**

Version: 1 Page 11 of 12 Revision date: 19/07/2016 Print date: 19/07/2016

H272 May intensify fire; oxidiser. H302 Harmful if swallowed. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410

### Classification codes:

Acute Tox. 4 [Oral]: Acute toxicity (Oral), Category 4

Aquatic Acute 1: Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1: Chronic effect to the aquatic environment, Category 1

Eye Dam. 1: Serious eye damage, Category 1 Eye Irrit. 2: Eye irritation, Category 2 Ox. Sol. 2: Oxidising solid, Category 2 Skin Irrit. 2: Skin irritant, Category 2

STOT SE 3: Specific target organ toxicity following a single exposure, Category 3

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

### Labelling in accordance with Directive 1999/45/EC:

### Symbols:





Corrosive



environment

R Phrases:

R8 Contact with combustible material may cause fire.

Harmful if swallowed. R22

R31 Contact with acids liberates toxic gas.

Causes severe burns. **R35** 

R37 Irritating to respiratory system.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S Phrases:

Keep away from combustible material. S17 S20 When using do not eat or drink.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S26

If swallowed, seek medical advice immediately and show this container or label. S46 Avoid release to the environment. Refer to special instructions/safety data sheets. S61

Keep locked up and out of the reach of children. S1/2

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

Contains: symclosene

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
87-90-1	symclosene	Registered
10043-01-3	Aluminiumsulfate	Registered
7758-99-8	copper sulphate pentahydrate	

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

(in accordance with Regulation (EU) 2015/830)



# **ASTRAL MULTIACTION GRANULAR**

 Version: 1
 Page 12 of 12

 Revision date: 19/07/2016
 Print date: 19/07/2016

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are

not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.