

Fitted Niq adjustable projector Proyector Niq empotrado orientable



Small projector with a stainless steel wall conduit.
Spotlight adjustable by up to 8°.

Proyector de pequeñas dimensiones con pasamuros de acero inoxidable. Punto de luz orientable 8°.

Consumption/ Consumo

Monocolour/ Monocolor: 4W (6VA)
Multicolour / Multicolor: 4W (7VA)
MDMX / MDMX: 4W (4VA)

Voltage/ Voltaje

Monocolour/ Monocolor: 12 Vac
Multicolour / Multicolor: 12 Vac
MDMX/ MDMX: 24 Vdc

Lumens/ Lúmenes

Monocolour/ Monocolor: 315 lm
Multicolour / Multicolor: 186 lm
MDMX/ MDMX: 186 lm

Efficiency/ Eficiencia

Monocolour/ Monocolor: 78,7 lm/W
Multicolour/ Multicolor: 46,5 lm/W
MDMX/ MDMX: 46,5 lm/W

Life Span/ Vida útil


L80 - 60.000h

Protection level/ Grado de Protección

IP68



I 1246 Fitted Niq adjustable projector
Proyector Niq empotrado orientable



Code/ Código	Light/ Luz	Face Plate/ Embellecedor	Optic/ Óptica	Control/ Control
I 1246	W Cool white Blanco frío WW Warm white Blanco cálido M Multicolour Multicolor MDMX Multicolour DMX Multicolor DMX	Material/ Material P Plastic Plástico I Stainless Steel Acero Inox. Shape/ Forma S Square Cuadrado R Round Redondo	N Narrow Concentrada M Medium Media W Wide Abierta	Multicolour Multicolor I0826 Modulator Modulador I0828 Remote control Control Remoto I0831 Push-button Pulsador DMX I0832DMX DMX power supply Alimentador DMX I0832DMXFE DMX external power supply Alimentador DMX fuente externa