

BOMBA DMX VARIABLE S

DMX VARIABLE PUMP S 1"



La bomba DMX Variable S permite controlar la altura de los surtidores individualmente, creando multitud de efectos y figuras en fuentes dinámicas. Es ideal para instalarse justo debajo de los surtidores tipo Spear Nozzle de 12 y 14 mm.

El equipo incorpora el sistema de variación de altura mediante protocolo DMX, lo que facilita el control de los surtidores y reduce considerablemente el tamaño y coste de los armarios eléctricos.

The DMX Variable Pump S allows to control the jet heights individually, creating a multitude of effects and figures in dynamic fountains. It is ideal to be installed just below the Spear Nozzle between 12 and 14 mm and Foamy Nozzles.

The device incorporates the height variation system through DMX protocol, what facilitates the control of the jets and reduces considerably the size and cost of electrical cabinets.

DMX VARIABLE PUMP S

Código / Code: **67410**

Dimensiones (L x W x H) [mm]	254 x 97 x 121	Dimensions (L x W x H) [mm]	254 x 97 x 121
Voltaje Nominal[V]	24 VDC	Nominal voltage [V]	24 VDC
Potencia [W]	100	Power [W]	100
Corriente Nominal [A]	4,2	Power rating [A]	4,2
Conexión hidráulica	1-1/2" G	Hydraulic connection	1-1/2" G
Profundidad mínima agua [mm]	200	Minimum water depth [mm]	200
Presión máxima [m]	5	Maximum pressure [m]	5
Caudal máximo [l/min]	160	Maximum flow [l/min]	160
Respuesta dinámica 0-100% [s]	1	Dynamic response 0-100% [s]	1
Arranques por minuto (máx.)	6	Starts per minute (max.)	6
Sistema de control	DMX-RDM	Control system	DMX-RDM
Peso [kg]	2	Weight [kg]	2

'19

NOVEDAD | NEW

FLUIDRA
INDUSTRY
METALAST

