

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 1 of 12  
Print date: 10/02/2020

### SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: ASTRAL MULTI-ACTION TABLETA 200 ANTICAL  
Product Code: 0391AZE

#### 1.2 Relevant identified uses of the mixture and uses advised against.

Desinfectant-algaecide-flocculant

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **FLUIDRA COMMERCIAL, S.A.U.**  
Address: Avda. Francesc Macià, 60, 20ª planta  
City: 08208 Sabadell (Barcelona) Spain  
Province: Barcelona  
Telephone: Tel:34 93 724 39 00 Fax:34 93 724 29 93  
Fax: +34 93 713 41 11  
E-mail: fds@inquide.com  
Web: www.astralpool.com

#### 1.4 Emergency telephone number:

Anti poisoning centre:

ITALY (Rome): 06/305 43 43

ITALY (Milan): 02/66 10 10 29

SPAIN: +34 91 562 04 20

FRANCE (Paris): 01 40 05 48 48 FRANCE (Toulouse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25

PORTUGAL: 808 250 143

BELGIQUE (Brussel): (+34) 070 245 245

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4 : Harmful if swallowed.

Aquatic Acute 1 : Very toxic to aquatic life.

Aquatic Chronic 1 : Very toxic to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation.

STOT SE 3 : May cause respiratory irritation.

STOT SE 3 : May cause drowsiness or dizziness.

#### 2.2 Label elements.

**Labelling in accordance with Regulation (EU) No 1272/2008:**

Pictograms:



Signal Word:

**Warning**

H statements:

H302

Harmful if swallowed.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 2 of 12  
Print date: 10/02/2020

H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H410 Very toxic to aquatic life with long lasting effects.

P statements:

P261 Avoid breathing dust.  
P271 Use only outdoors or in a well-ventilated area.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P264 Wash hands thoroughly after handling.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P102 Keep out of reach of children.  
P405 Store locked up.  
P273 Avoid release to the environment.  
P391 Collect spillage.  
P501 Dispose of contents/container in accordance with applicable regulations.

EUH statements:

EUH031 Contact with acids liberates toxic gas.  
EUH206 Warning! Do not use together with other products. May release dangerous gases (chlorine).

Contains:

symclosene  
copper sulphate pentahydrate

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 613-031-00-5 CAS No: 87-90-1 EC No: 201-782-8	symclosene	80 - 100 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Irrit. 2, H319 - Ox. Sol. 2, H272 - STOT SE 3, H335	-
Index No: 005-007-00-2 CAS No: 10043-35-3 EC No: 233-139-2 Registration No: 01-2119486683-25-XXXX	[4] boric acid	0.3 - 5.5 %	Repr. 1B, H360FD	Repr. 1B, H360FD: C ≥ 5,5 %
CAS No: 10043-01-3 EC No: 233-135-0 Registration No: 01-2119531538-36-XXXX	Aluminium sulfate	1 - 3 %	Eye Dam. 1, H318	-

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 3 of 12  
Print date: 10/02/2020

Index No: 029-023-00-4 CAS No: 7758-99-8 EC No: 231-847-6	copper sulphate pentahydrate	1 - 10 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 (M=10) - Aquatic Chronic 1, H410 - Eye Dam. 1, H318	-
---	------------------------------	----------	--	---

(\* ) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

[4] Substance included in the list established under Article 59, paragraph 1, REACH (Candidate or subject to authorization).

### SECTION 4: FIRST AID MEASURES.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

#### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

### SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

#### 5.1 Extinguishing media.

##### Suitable extinguishing media:

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray.

##### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

Suitable extinguishing media: CO<sub>2</sub> in small fires and water in large quantities (small amounts of water may aggravate the situation)

Unsuitable extinguishing media: Dry powder, Halogenated hydrocarbon, ABC powder.

#### 5.2 Special hazards arising from the mixture.

##### Special risks.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 4 of 12  
Print date: 10/02/2020

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

The contaminated area should be immediately cleaned with an appropriate de-contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers at room temperature, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P8	OXIDISING LIQUIDS AND SOLIDS	50	200
E1	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200

### 7.3 Specific end use(s).

None in particular.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 5 of 12  
Print date: 10/02/2020

### 8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
boric acid CAS No: 10043-35-3 EC No: 233-139-2	DNEL (Workers)	Inhalation, Long-term, Systemic effects	8,3 (mg/m <sup>3</sup> )
Aluminium sulfate CAS No: 10043-01-3 EC No: 233-135-0	DNEL (Workers)	Dermal, Long-term, Local effects	10 (mg/kg)
	DNEL (General population)	Oral, Long-term, Systemic effects	5 (mg/kg)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	1,8 (mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
Aluminium sulfate CAS No: 10043-01-3 EC No: 233-135-0	Water (freshwater)	34,6 (mg/kg)
	Sediment (marine water)	3,46 (mg/kg)
	Soil	33,1 (mg/kg)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

CAS: 87-90-1

TLV TWA - 0.5 ppm (1.5 mg/m<sup>3</sup>) Cl gas

TLV STEL - 1 ppm (3.0 mg/m<sup>3</sup>) Cl gas

CAS: 10043-01-3

TLV TWA - 2 mg/m<sup>3</sup> (Al)

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>	
<b>Uses:</b>	<b>Desinfectant-algaecide-flocculant</b>	
<b>Breathing protection:</b>		
PPE:	Filter mask for protection against gases and particles.	
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.	
CEN standards:	EN 136, EN 140, EN 405	
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.	
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.	
Filter Type needed:	A2	
<b>Hand protection:</b>		
PPE:	Protective gloves against chemicals.	
Characteristics:	«CE» marking, category III.	
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420	
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.	
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.	

-Continued on next page.-

# SAFETY DATA SHEET



(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 6 of 12  
Print date: 10/02/2020

Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
<b>Eye protection:</b>					
PPE:	Protective goggles with built-in frame.				
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.				
CEN standards:	EN 165, EN 166, EN 167, EN 168				
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.				
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.				
<b>Skin protection:</b>					
PPE:	Chemical protective clothing				
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.				
CEN standards:	EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.				
PPE:	Work footwear.				
Characteristics:	«CE» marking, category II.				
CEN standards:	EN ISO 13287, EN 20347				
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.				
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident				

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Appearance: Tablets  
Colour: White and blue  
Odour: Similar to bleach  
Odour threshold: N.A./N.A.  
pH: 2,1 - 3 (1%)  
Melting point: > 230 °C  
Boiling Point: 225 °C  
Flash point: N.A./N.A.  
Evaporation rate: N.A./N.A.  
Inflammability (solid, gas): > 250 °C  
Lower Explosive Limit: N.A./N.A.  
Upper Explosive Limit: N.A./N.A.  
Vapour pressure: 0,908  
Vapour density: N.A./N.A.  
Relative density: 1,379 g/cm<sup>3</sup>  
Solubility: N.A./N.A.  
Liposolubility: N.A./N.A.  
Hydrosolubility: N.A./N.A.  
Partition coefficient (n-octanol/water): N.A./N.A.  
Auto-ignition temperature: N.A./N.A.  
Decomposition temperature: N.A./N.A.  
Viscosity: N.A./N.A.  
Explosive properties: N.A./N.A.  
Oxidizing properties: Si

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

#### 9.2 Other information.

Pour point: N.A./N.A.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 7 of 12  
Print date: 10/02/2020

Blink: N.A./N.A.  
Kinematic viscosity: N.A./N.A.  
N.A./N.A. = Not Available/Not Applicable due to the nature of the product

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

Contact with acids liberates toxic gas.

#### 10.2 Chemical stability.

Unstable in contact with:

- Bases.

#### 10.3 Possibility of hazardous reactions.

Warning! Do not use together with other products. May release dangerous gases (chlorine).  
Neutralization can occur on contact with bases.

#### 10.4 Conditions to avoid.

- Avoid contact with bases.

#### 10.5 Incompatible materials.

Avoid the following materials:

- Bases.

#### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- Corrosive vapors or gases.

### SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splatters in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

#### 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

#### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
symclosene CAS No: 87-90-1      EC No: 201-782-8	Oral	LD50 [1] EPA OPP 81-1	Rat	490 mg/kg [1]
	Dermal	LD50 [1] EPA OPP 81-2	Rabbit	>2000 mg/kg [1]
	Inhalation			
boric acid CAS No: 10043-35-3      EC No: 233-139-2	Oral	LD50 LD50 [1] JAMA, Journal of the American Medical Association. Vol. 128, Pg. 266, 1945	Rat Rat	3500-4100 mg/kg 2660 mg/kg bw [1]
	Dermal	LD50	Rabbit	>2000 mg/kg
	Inhalation	LC50	Rat	> 2 mg/l
Aluminium sulfate	Oral	LD50 [1] OCDE 401	Rat	>2000 mg/kg [1]
	Dermal	LD50	Rabbit	>5000 mg/kg [1]

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 8 of 12  
Print date: 10/02/2020

CAS No: 10043-01-3    EC No: 233-135-0		[1] OCDE 402
	Inhalation	

a) acute toxicity;  
Product classified:  
Acute toxicity (Oral), Category 4: Harmful if swallowed.

b) skin corrosion/irritation;  
Not conclusive data for classification.

c) serious eye damage/irritation;  
Product classified:  
Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;  
Not conclusive data for classification.

e) germ cell mutagenicity;  
Not conclusive data for classification.

f) carcinogenicity;  
Not conclusive data for classification.

g) reproductive toxicity;  
Based on available data, the classification criteria are not met.

h) STOT-single exposure;  
Product classified:  
Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;  
Not conclusive data for classification.

j) aspiration hazard;  
Not conclusive data for classification.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
symclosene  CAS No: 87-90-1    EC No: 201-782-8	Fish	LC50	Fish	0.32 mg/l (96h)
	Aquatic invertebrates	LC50	Daphnia	0.21 mg/l (48h)
	Aquatic plants			
boric acid	Fish	LC50	Fish	74 mg/l (96 h)
		LC50	Fish	487 mg/l (96 h) [1]
	Aquatic invertebrates	LC50	Daphnia	133 mg/l (48 h)
		LC50	Crustacean	180 mg/l (48 h) [1]

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 9 of 12  
Print date: 10/02/2020

		[1] Gersich, F.M. 1984. Evaluation of a Static Renewal Chronic Toxicity Test Method for Daphnia magna Straus Using Boric Acid. Environ.Toxicol.Chem. 3(1):89-94. Lewis, M.A., and L.C. Valentine 1981. Acute and Chronic Toxicities of Boric Acid to Daphnia magna Straus. Bull.EnvIRON.Contam.Toxicol. 27(3):309-315		
CAS No: 10043-35-3 EC No: 233-139-2	Aquatic plants			
Aluminium sulfate	Fish	LC50	Fish	> 1000 mg/l (96 h)
	Aquatic invertebrates	LC50	Daphnia	> 160 mg/l (48h)
	Aquatic plants			
CAS No: 10043-01-3 EC No: 233-135-0				

### 12.2 Persistence and degradability.

There is no information available on the degradability of the substances present.

No information is available regarding the degradability of the substances present.No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## SECTION 13 DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 10 of 12  
Print date: 10/02/2020

### 14.1 UN number.

UN No: UN3077

### 14.2 UN proper shipping name.

Description:

ADR: UN 3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS SYMCLOSENE), 9, PG III, (-)

IMDG: UN 3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS SYMCLOSENE), 9, PG III, MARINE POLLUTANT

ICAO/IATA: UN 3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (CONTAINS SYMCLOSENE), 9, PG III

### 14.3 Transport hazard class(es).

Class(es): 9

### 14.4 Packing group.

Packing group: III

### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

### 14.6 Special precautions for user.

Labels: 9



Hazard number: 90

ADR LQ: 5 kg

IMDG LQ: 5 kg

ICAO LQ: 30 kg B

Provisions concerning carriage in bulk ADR:

VC1 Carriage in bulk in sheeted vehicles, sheeted containers or sheeted bulk containers is permitted.

VC2 Carriage in bulk in closed vehicles, closed containers or closed bulk containers is permitted.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F

Proceed in accordance with point 6.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P8,E1

Information related to Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products:

Product Type	Group
--------------	-------

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3

Revision date: 14/01/2020

Page 11 of 12

Print date: 10/02/2020

Disinfectants and algaecides not intended for direct application to humans or animals	Disinfectants
---	---------------

Active substances	Concentration %
symclosene CAS No: 87-90-1 EC No: 201-782-8	80 - 100
copper sulphate pentahydrate CAS No: 7758-99-8 EC No: 231-847-6	1 - 10

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
30. Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 classified as toxic to reproduction category 1A or 1B (Table 3.1) or toxic to reproduction category 1 or 2 (Table 3.2) and listed as follows: - Reproductive toxicant category 1A adverse effects on sexual function and fertility or on development (Table 3.1) or reproductive toxicant category 1 with R60 (May impair fertility) or R61 (May cause harm to the unborn child) (Table 3.2) listed in Appendix 5 - Reproductive toxicant category 1B adverse effects on sexual function and fertility or on development (Table 3.1) or reproductive toxicant category 2 with R60 (May impair fertility) or R61 (May cause harm to the unborn child) (Table 3.2) listed in Appendix 6	1. Shall not be placed on the market, or used, - as substances, - as constituents of other substances, or, - in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: - either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, - the relevant concentration specified in Directive 1999/45/EC where no specific concentration limit is set out in Part 3 of Annex VI to Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: 'Restricted to professional users'. 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: - motor fuels which are covered by Directive 98/70/EC, - mineral oil products intended for use as fuel in mobile or fixed combustion plants, - fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Directive 1999/45/EC; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date.

Kind of pollutant to water (Germany): Not dangerous to water. (Autoclassified according to the AwSV Regulations)

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H272	May intensify fire; oxidiser.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H360FD	May damage fertility. May damage the unborn child.
H400	Very toxic to aquatic life.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 0391AZE-ASTRAL MULTI-ACTION TABLETA 200 ANTICAL



Version: 3  
Revision date: 14/01/2020

Page 12 of 12  
Print date: 10/02/2020

H410 Very toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Oral), Category 4  
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1  
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1  
Eye Dam. 1 : Serious eye damage, Category 1  
Eye Irrit. 2 : Eye irritation, Category 2  
Ox. Sol. 2 : Oxidising solid, Category 2  
Repr. 1B : Reproductive toxicant, Category 1B  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
AwSV: Facility Regulations for handling substances that are hazardous for the water.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.  
WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.